

Underceiling & Floor Standing

Cooling & Heating

Features



Waterproof



Auto Swing & Wide angle airflow



Auto-restart



24 hr timing



Auto defrost



Easy-washable and easy-moveable filter



Elegant design

A U C 3 6
A U C 4 8
A U C 6 0

Technical Data

Model		AUC 36	AUC 48	AUC 60
Function		Cooling/Heating	Cooling/Heating	Cooling/Heating
Capacity	W	10 500/11 400	14 070/15 535	17 585/19 930
	BTU	36 000/39 000	48 000/53 000	60 000/68 000
Electrical Data		V, Hz, Ph	380, 50, 3	380, 50, 3
Running Current	Cooling	A	6.5	8.2
	Heating	A	5.8	8.6
Starting Current		A	59	59
Air Flow Volume		(m ³ /h)	1 600/1 200/1 000	2 000/1 800/1 600
Noise Levels		dB(A)	45/43/40	47/46/40
Max pipe run		m	25	30
Max difference in (v)		m	10	15
Refrigerant piping		inch	0.5/0.75	0.5/0.75
Liquid line/gas line				
Net Weight in/out		(Kg)	35/112	52/114
Gross Weight in/out		(Kg)	40/127	59/127
Dimensions net In Unit		WxHxD(mm)	1 285 x 660 x 198	1 670 x 680 x 240
Dimensions net Out Unit		WxHxD(mm)	990 x 960 x 360	990 x 960 x 360
Dimension In Packaged		WxHxD(mm)	1 379 x 744 x 296	1764 x 760 x 330
Dimension Out Packaged		WxHxD(mm)	1 120 x 1 090 x 435	1 120 x 1 090 x 435
Gas			R22	R22

* The data is subject to modification without notice.



Distributed by:
Fourways Airconditioning
011 704 6320
Clorpique
031 579 1895
SamAir
021 556 8292

AllianceAir
AllianceAir